M-85 Series

Single-Hung (side load), Horizontal Slider & Fixed 2³/₄" Nominal Frame Depth



Horizontal Slider Single Vent



Quality Windows & Doors for All Seasons

Performance and efficiency in a cost-effective choice for new construction and renovation

Structural Thermal Break: Pour and debridge thermal break, utilizing Azo-Brader[™] Technology with a 10-year warranty against failure of the polymer

3/4" Sealed Insulated Glass (1" on Fixed): 10-year limited warranty. Numerous glass options available including Low-E, tinted, obscure, tempered, laminated, argon-filled and spandrel

- Commercial-grade aluminum extrusions offer strength with a solid, attractive appearance
- Custom installation accessories including receptors and subsills, face flange, nail fins, panning, snap trim and mullions
- Aluminum screen frame with fiberglass cloth standard optional aluminum cloth
- Self-lock feature is standard, minimum Grade 10 forced entry resistance. Sweep lock available as an option
- Ergonomically designed lift and pull rails on operable sash
- Standard finishes include white or bronze (AAMA 2603); and clear or dark bronze anodized (AAMA 611). White or bronze 2-coat Kynar[®] (AAMA 2605) available with minimum order Other non-standard colors with minimum order


(Kynar® is a registered trademark of Arkema Inc.) (Azo-Brader™ is a trademark of Azon USA Inc.)







Cross-Sections and Additional Features




trapezoid, and more



r products feature a pour and debridge polyurethane thermal break for better performance, utilizing Azo-Brader™ technology with a 10-year warranty against failure of the polymer.





Visit www.wojan.com/products to view and download detailed elevation drawings.

All Wojan products carry warranties of 1 year on window materials and workmanship, 10 years on the IGU and 10 years on the thermal break.

Ask about extended warranty bundles.

Product Performance Details

Туре	Product Designation [♣] ♥	Structural/Water/ Air Test Size (W x H)	Air Infiltration (cfm/sq ft)	Water Resistance (psf)	Deflection (psf)	Structural (psf)
Single-Hung	CW30	56"W x 91"H	0.01 @ 1.6 psf	4.60	30	45
	optional: CW50	52"W x 81"H		7.52	50	75
Horizontal Slider Single Vent (XO)	LC25	71"W x 60"H	0.18 @ 1.6 psf	3.76	25	37.5
	optional: CW30			4.60	30	45
Horizontal Slider with subsill Single Vent (XO)	CW35	72"W x 60"H	0.12 @ 1.6 psf	5.43	35	52.5
	optional: C50			7.52	50	75
Fixed Hurricane-Impact Also Available!	CW30	60"W x 72"H	< .01 @ 1.57 psf	4.60	30	45
	optional: CW50		< .01 @ 1.6 psf	7.52	50	75
	optional: CW65		< .01 @ 1.57 psf	9.82	65	97.5

[🍨] The '05 fenestration standard utilized five performance classes: R, LC, C, HC and AW. NAFS-08 and -11 utilize four such classes: R, LC, CW and AW.


Factory Stacked Integrated Louver

All M-85 over louver configurations are factory stacked with an integral nailing fin for easy installation, and available with the same features and options as the standard models.



Fixed over Louver configuration is factory stacked with an integral nailing fin in one master frame

Contact our office or your Wojan Sales Representative for more details.



HQ/Sales/Manufacturing 217 Stover Road Charlevoix, MI 49720 (800) 632-9827 | fax (231) 547-4237



www.wojan.com

Manufacturing 340 Jay Street Coldwater, MI 49038 (866) 378-2202 | fax (517) 279-9832

Many window ratings can be increased by downsizing the window and determining maximum performance through testing. Contact your local Wojan sales representative or our office for details.